


Documents corresponding to the product:

Standard EN 60947-4-1



Dimensions (mm)

H	W	L	W1	W2
32	40	35	26	45
H2	L1	L2		
48	6,5	37		

AUXILIARY CONTACTS

AUXILIARY CONTACTS

At necessity the element provide auxiliary number of contacts. They are specially designed for mounting on the movable part of the magnetic core of the contactors LT 1K/D series.

FUNCTIONS:

- extending the number of the operative contactors up to 4 in different
- Combinations
 - switches on simultaneously with the other contact system of the contactor
- Operation class: AC 3

- insulation voltage: 690V
- Joining terminal: screw terminal
- Connecting:
 - flexible conductors with or without cable terminal
 - rigid conductors

MOUNTING:

- on the movable cover of the contactor through pinching
- mounting position: vertical gradient – maximum $\pm 5^\circ$
- Plastic: wear resistance of UV rays and non-flammable (self-extinguishing material)

Type	For Contactor Series	Number of contacts	Rated current	Section of the conductor (mm ²)	Product category	Catalogue number
LT01-DN02	LT1-D & LT1-F	2NC	6A	0,5-1	B	23002
LT01-DN11	LT1-D & LT1-F	NO+NC	6A	0,5-1	B	23011
LT01-DN20	LT1-D & LT1-F	2NO	6A	0,5-1	B	23020
LT01-DN22	LT1-D & LT1-F	2NO+2NC	6A	0,5-1	B	23022
LT01-DN40	LT1-D & LT1-F	4NO	6A	0,5-1	B	23040
LT01-DN04	LT1-D & LT1-F	4NC	6A	0,5-1	B	23004
LT01-KN11	LT1-HK	NO+NC	6A	0,5-1	B	23001
LT01-KN22	LT1-HK	2NO+2NC	6A	0,5-1	B	23003