



Single-deck terminal block - Left side for CEM22-V - Pitch 5mm - 2 poles

GENERAL INFORMATION

pitch:	5 mm
housing height:	15,30 mm
housing depth:	9.5 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.7 × 2.7 mm
wire stripping:	max 7 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
recommended torque:	0.5÷0.55 Nm / 4.5÷4.9 in.lbs

APPROVALS DATA



EN 60998-1

current:	16A
voltage:	250V
wire section:	2,5mm ²
torque:	0,5Nm

FILE: CA02.01614



-

-

-

-

-

-



UL 1059

15A factory / 15A field

300V

14÷30AWG

4,5Lb-in

E178356

MATERIALS

housing: PA - UL 94 V0

AVAILABLE COLOURS

screw:
clamp/spring:
terminal:

Galvanized steel
Nickel copper alloy
Tin-plated copper alloy

GN **GY** (STD) **BK** **BL** **RD** **YL** **OG**

other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	ML252-5-S-LC	N/A	N/A	N/A