



## Male plug-in connector - Stackable version - Pitch 3,5mm - Poles 02÷24

### GENERAL INFORMATION

pitch:	3,5 mm
housing height:	14,00 mm
housing depth:	2.8 mm
dimensional class:	slow
wire section:	-
clamp opening size:	-
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	8A
voltage:	160V
impulse voltage:	2.5 kV

### MECHANICAL CHARACTERISTICS

### APPROVALS DATA



current:  
voltage:  
FILE:

-  
-  
-

-  
-  
-

-  
-  
-

### ADDITIONAL INFORMATIONS

SCIP NUMBER:

e7871ea5-2cf8-4f17-b626-38a85b04faba

### MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a
terminal:	Tin-plated copper alloy

### AVAILABLE COLOURS

<b>BK</b> (STD)	
other colours:	upon request

<b>poles</b>	<b>P/N</b>	<b>pcs/pack</b>	<b>W [Kg]*</b>	<b>W [Kg]*</b>
--------------	------------	-----------------	----------------	----------------

02	PVS02-3,5	N/A	N/A	N/A
03	PVS03-3,5	N/A	N/A	N/A
04	PVS04-3,5	N/A	N/A	N/A
05	PVS05-3,5	N/A	N/A	N/A
06	PVS06-3,5	N/A	N/A	N/A
07	PVS07-3,5	N/A	N/A	N/A
08	PVS08-3,5	N/A	N/A	N/A
09	PVS09-3,5	N/A	N/A	N/A
10	PVS10-3,5	N/A	N/A	N/A
11	PVS11-3,5	N/A	N/A	N/A
12	PVS12-3,5	N/A	N/A	N/A
13	PVS13-3,5	N/A	N/A	N/A
14	PVS14-3,5	N/A	N/A	N/A
15	PVS15-3,5	N/A	N/A	N/A
16	PVS16-3,5	N/A	N/A	N/A
17	PVS17-3,5	N/A	N/A	N/A
18	PVS18-3,5	N/A	N/A	N/A
19	PVS19-3,5	N/A	N/A	N/A
20	PVS20-3,5	N/A	N/A	N/A
21	PVS21-3,5	N/A	N/A	N/A
22	PVS22-3,5	N/A	N/A	N/A
23	PVS23-3,5	N/A	N/A	N/A
24	PVS24-3,5	N/A	N/A	N/A