



Panel feed-through terminal block - Fixed by nut - Modular version - Hooked terminal - Pitch 10mm - 1 pole

GENERAL INFORMATION

pitch:	10 mm
housing height:	209,00 mm
housing depth:	11.2 mm
dimensional class:	high
wire section:	4.0 mm ² / 12 AWG
clamp opening size:	Ø7.2 mm
wire stripping:	max 10 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	32A
voltage:	450V
test voltage:	2.5 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2
recommended torque:	0.5÷0.55 Nm / 4.5÷4.9 in.lbs

APPROVALS DATA



EN 60998-1

current:	32A
voltage:	450V
wire section:	4.0mm ²



EN 60998-1

current:	32A
voltage:	450V
wire section:	4.0mm ²



UL 1059

current:	36A factory / 30A field
voltage:	600V
wire section:	10÷30AWG

torque:	0.5Nm	0.5Nm	4.5Lb-in
FILE:	CA02.00601	40014733	E178356

ADDITIONAL INFORMATION

SCIP NUMBER: 695f1aab-9175-490a-bf35-098dac716cf3

MATERIALS

housing: PA - UL 94 V0
 screw: Galvanized steel
 clamp/spring: Nicked copper alloy
 terminal: Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MPT410-D-U	N/A	N/A	N/A